

ARTICLES: ROSINI COLLECTION

RESISTENCIA DE LAS COSTURAS SEAM STRENGTH	URDIMBRE/ TRAMA/ Weft: 4,1 mm.	Warp : 3,8 mm	BS 3320:1988 BS 2543:1995
RESISTENCIA A LA ABRASIÓN ABRASIÓN RESISTANCE	CICLOS: > 24.000 CYCLES : > 24.000		BS 5690 BS 2543:1995
SOLIDEZ DE LOS COLORES A LA LUZ : 5 COLOUR FASTNESS TO LIGHT			UNE 40187 BS 1006-B02
SOLIDEZ A LA LIMPIEZA EN SECO : 4 / 5 RUBBING SOLVENTS			ISO 105-D01 UNE 40099
SOLIDEZ DE LOS COLORES AL LAVADO : 4 / 5 RUBBING FASTNESS IN HUMID STATE			ISO 105-C06 UNE 40029
RESISTENCIA AL PILLING : 4 PILLING RESISTANCE			ISO/DIS 12945-2

INSTRUCCIONES DE LAVADO

WASHING INSTRUCTIONS

- A MANO MAX. 30°C CON DETERGENTES NEUTROS
- HAND WASH AT A MAX. OF 30° C. USING NEUTRAL DETERGENTS ONLY.
- NO ESCURRIR, RETO RCER NI CENTRIFUGAR
- DO NEITHER SQUEEZE, NOR WRING, NOR CENTRIFUGATE THE FABRIC.
- NO USAR LEJÍA.
- DO NOT USE BLEACH.
- EVITAR SECAR AL SOL.
- AVOID DRYING IN THE SUN.
- PLANCHAR POR LA CARA PO STERIOR, MAX. 110° C.
- IRON ONLY ON THE REAR SIDE, AT A MAXIMUM OF 110° C.
- PUEDE UTILIZARSE EL LAVADO EN SECO.
- DRY CLEANING CAN ALSO BE USED.

